



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Termopar con aislamiento mineral con olla roscada y 100 mm de cable IEC de doble torsin con aislamiento de PFA - Tipos K, J, T, N



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Termopar con aislamiento mineral en varias longitudes terminadas con 100 mm, IEC doble trenzado con aislamiento de PFA, 7/0,2 mm.

Necesita calibrar su sensor de temperatura?

Trazable a los estándares de calibración ISO17025 (UKAS), Labfacility ofrece la opción de una calibración trazable de 3 o 5 puntos utilizando nuestras instalaciones de calibración internas.

Tenga en cuenta que si agrega una opción de calibración a su pedido, se comunicará con usted con respecto a la información de entrega.

Características técnicas

Specifications

General Description	Mineral insulated thermocouple in various lengths terminated with 100mm,PFA insulated twin twisted IEC,7/0.2mm.
Sensor Type	Mineral Insulated
Thermocouple Type	K,J,T,N
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	1.0, 1.5, 3.0, 4.5 & 6.0mm
Probe Length	150, 250, 500, 1000, 1500 & 2000mm
Sheath Material	K - Stainless steel 310, J - Stainless steel 321, T - Stainless steel 316, N - Nicrosil
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (200°C)
Cable Length	100mm
Cable Type	PFA insulated twin twisted IEC
Core / Strands	7/0.2mm



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Termination Type	Bare tails
Max. Temperature	K +1100°C for 1.5 & 3.0mm diameters +750°C for 1.0mm diameter, J +760°C, T +400°C, N +1300°C.
Min. Temperature	K -40°C, J -100°C, T -100°C, N -100°C
Standards Met	In accordance with IEC 584