

Termmetro intelligente TempTest 1 (Tipo K)



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Termómetros inteligentes Temptest con pantalla giratoria nica.

El termómetro Temptest est alojado en una carcasa impermeable IP67 con un sello de goma ergonmico, ambos incluyen el aditivo 'Biomaster' para reducir el crecimiento bacteriano. Adems de ser resistente al agua, es "probablemente" uno de los termómetros de contacto de lectura ms rpida del mercado actual. La temperatura real de un producto se puede medir en solo tres segundos.

Se muestran tanto la batera baja (icono) como la indicacin de circuito abierto, cuando corresponda. Cada Temptest funciona con dos pilas AAA con una vida til mnima de 5000 horas en uso normal sin retroiluminacin. La funcin de retroiluminacin cuenta con tecnologa inteligente, que solo se enciende cuando el nivel de luz lo requiere.

El Temptest 1 se suministra con una sonda de penetracin de alimentos de acero inoxidable integrada y fijada permanentemente (3,3 x 80 mm) con punta de respuesta rpida.

Caractersticas tcnicas

Specifications

Product Code	XE-3987-001
General Description	Fast response probe, reaches temperature in just 3 seconds! Patented, automatic 360° rotational display Small, compact, waterproof (IP67) design Intelligent backlit display
Type	The Temptest 1 is supplied with an integral, permanently attached, stainless steel food penetration probe (Ø3.3 x 80 mm) with fast response tip
Thermocouple Type	Type K
Accuracy	±0.4°C (-49.9 to 200 °C) otherwise ±1 °C
Resolution of data display	Resolution 0.1 °C/°F
Dimensions	17 x 47 x 120mm
Max. Temperature	299.9°C
Min. Temperature	-49.9°C
Power Supply	Battery 2 x 1.5 volt AAA. Battery life 5000 hours (normal use, without backlight)



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Weight	105 grams
--------	-----------