

## Sonda industrial Platinum Resistance Pt100 con extensin de revestimiento. Sonda de 250 mm x 8,0 mm con inserto de 375 mm x 6,0 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

**Necesita calibrar su sensor de temperatura?**

Trazable a los estándares de calibración ISO17025 (UKAS), Labfacility ofrece la opción de una calibración trazable de 3 o 5 puntos utilizando nuestra instalación de calibración interna, puede seleccionar cualquier punto de temperatura entre -10 C y +200 C.

**Tenga en cuenta que si agrega una opción de calibración a su pedido, nos pondremos en contacto con usted con respecto a la información de entrega.**

**Características técnicas****Specifications**

<b>Product Code</b>	XE-3641-001
<b>Sensor Type</b>	Pt100 (100 Ohms @ 0°C) to IEC 751
<b>Insert</b>	6.0mm diameter 316 stainless steel terminated with spring loaded ceramic connection block
<b>Process Connection</b>	1/2"BSP parallel
<b>Cable Connection</b>	M20 x 1.5mm cable entry (gland included)
<b>Termination Type</b>	IP67 aluminium alloy weatherproof KNE connection head
<b>Max. Temperature</b>	+450°C (connection head @ 170°C)
<b>Min. Temperature</b>	-50°C
<b>Tolerance</b>	Class B
<b>Number of Wires</b>	4
<b>Probe Material</b>	8.0mmO 316 stainless steel below 1/2"BSP parallel process connection 1/2" diameter x 75mm lagging length to underside of connection head