

**0,75 mm de diametro con enchufe ANSI en
miniatura: aislado o conectado a tierra**



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Tipo K Acero inoxidable 316 con aislamiento mineral, equipado con minitapn

Si requiere cantidades mayores, enve un correo electronico sales@labfacility.com o llame a nuestra lnea de ventas 01243 871280.

Necesita calibrar su sensor de temperatura?

Trazable a los estndares de calibracin ISO17025 (UKAS), Labfacility ofrece la opcin de una calibracin trazable de 3 o 5 puntos utilizando nuestras instalaciones de calibracin internas.

Tenga en cuenta que si agrega una opcin de calibracin a su pedido, se comunicar con usted con respecto a la informacin de entrega.

Caractersticas tcnicas

Specifications

| | |
|-----------------------------|--|
| General Description | Type K 316 stainless steel, Fitted with miniplug |
| Sensor Type | Mineral Insulated |
| Thermocouple Type | K |
| Element/hot junction | Single element, junction insulated or grounded from sheath |
| Probe Diameter | 0.75mm |
| Probe Length | 50, 100, 150, 250mm |
| Sheath Material | 316 stainless steel |
| Pot Type | Thermocouple ANSI Mini plug (Max Temp 200°C) |
| Max. Temperature | +750°C |
| Min. Temperature | -100°C |
| Tolerance | Class 1 |
| Standards Met | In accordance with ANSI MC96.1 |