

## 0,75 mm de diametro con colas desnudas: aisladas o conectadas a tierra



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

### Sondas de termopar de junta de transicin de dimetro fino

Las uniones de termopar estn disponibles como conectadas a tierra, para un tiempo de respuesta ms rpido y un menor costo; o aislado, para el aislamiento elctrico del termopar de la vaina.

Si requiere cantidades mayores, enve un correo electrnico sales@labfacility.com o llame a nuestra lnea de ventas 01243 871280.

### Necesita calibrar su sensor de temperatura?

Trazable a los estndares de calibracin ISO17025 (UKAS), Labfacility ofrece la opcin de una calibracin trazable de 3 o 5 puntos utilizando nuestras instalaciones de calibracin internas.

**Tenga en cuenta que si agrega una opcin de calibracin a su pedido, se comunicar con usted con respecto a la informacin de entrega. .**

### Caractersticas tcnicas

## Specifications

<b>Sensor Type</b>	Mineral Insulated
<b>Thermocouple Type</b>	K
<b>Element/hot junction</b>	Single element, junction insulated or grounded from sheath
<b>Probe Diameter</b>	0.75mm
<b>Probe Length</b>	100,150, 250mm
<b>Sheath Material</b>	K - Stainless steel 316
<b>Termination Type</b>	Fortfix sealed with = +VE leg 15mm long and -VE leg 10mm long
<b>Max. Temperature</b>	+650°C
<b>Min. Temperature</b>	-40°C
<b>Tolerance</b>	Class 1
<b>Standards Met</b>	In accordance with IEC 584